

"The aligned arrays represent an important step toward large-scale integrated nanotube electronics," said John A. Rogers, a Founder Professor of Materials Science and Engineering at Illinois, and corresponding author of a paper accepted for publication in the journal Nature Nanotechnology, and posted on i Web site.

To create nanotube arrays, the researchers begin with a wafer of single-crystal quartz, on which they deposit thin strips of iron nanoparticles. The iron acts as catalyst for the growth of carbon nanotubes by chemical vapor deposition. As t nanotubes grow past the iron strips, they lock onto the quartz crystal, which th aligns their growth.

The resulting linear arrays consist of hundreds of thousands of nanotubes, eacl approximately 1 nanometer in diameter (ananometer is 1 billionth of a meter), and up to 300 microns in length (a micron is 1 millionth of a meter). The nanotubes are spaced approximately 100 nanometers apart.

The arrays function as an effective thin-film semiconductor material in which charge moves independently through each of the nanotubes. In this configuration, the nanotubes can be integrated into electronic devices in a straightforward fashion by conventional chip-processing techniques.

A typical device incorporates approximately 1,000 nanotubes, and can produce current outputs 1,000 times higher than those of previously reported devices that incorporate just a single nanotube. Many devices can be built from each array, with good device-to-device uniformity. Detailed theoretical analysis of these unusual devices reveals many aspects of their operation.

Using the arrays, the researchers built and tested a number of transistors and logic gates, and compared the properties of nanotube arrays with those of individual nanotubes.

"This is the first study that shows properties in scalable device configurations that approach the intrinsic properties of the tubes themselves, as inferred from single-tube studies," said Rogers, who also is a researcher at the university's Beckman Institute.

Nanotube arrays aren't likely to replace silicon, Rogers said, but could be adde to a silicon chip and exploited for particular purposes, such as higher speed operation, higher power capacity and linear behavior for enhanced functionality They can also be used in applications such as flexible devices, for which silicon not well suited.

"Nanotubes have shown potential in the past, but there hasn't been a clear pat from science to technology," said Moonsub Shim, a professor of materials scier and engineering at Illinois, and a co-author of the paper. "Our work seeks to bridge this gap."

With Rogers and Shim, co-authors of the paper are postdoctoral research associate Seong Jun Kang and graduate students Coskun Kocabas and Taner Ozel, all at Illinois; electrical and computer engineering professor Muhammad / Alam and graduate student Ninad Pimparkar at Purdue, and physics professor Slava V. Rotkin at Lehigh. Posted July 2nd, 2007 Nanotechnology News Archive

🗉 ba



AZoNano is grateful for the support provided by our sponsors to both AZoNano.com and to the author and peer reviewers of AZoJono -Journal of Nantechnology Online - open access to leading Nanotech Scie

Please visit our sponsors page or click the links below to view the world leading products and services c sponsors have to offer. To discuss an AZoNano sponsor package please contact our Sales and Marketing Mi





Other AZoNetwork Sites | AZoM.com | AZoBuild.com | News-Medical.Net

HOME >	TERMS >	MATERIALS >	APPLICATIONS >	INDUSTRI
ABOUT >	HELPS/FAQS >	CLASSIFIEDS >	COURSES >	EVENTS
SPONSORS >	NEWSLETTER >	JOBS >	NANO JOURNAL >	NEWS

AZoNano - The A to Z of Nanotechnology...Copyright © 2007 by AZoM.com Pty.Ltd