

[Login](#) | [Register](#)



Answers for infrastructure.

[> Click here for your life science solutions guide](#)

SIEMENS

[Publications](#) [Sections](#) [News](#) [Community](#) [Multimedia](#) [Awards](#) [Subscribe](#)

[Advanced Search](#)

[Home](#) > [News](#)

[RSS Feeds](#) [Newsletters](#) [Bookmark](#)

Advertisement

[\[-\] Text](#) [\[+\]](#)

## Ultrathin LEDs create new classes of lighting

Posted In: [R&D Daily](#) | [Energy Solutions](#) | [Electrical Materials](#) | [Glass](#) | [Organic Materials](#) | [Thin films](#) | [Engineering](#) | [Material Science](#) | [Electrical](#) | [Engineering](#) | [Materials](#) | [Optics](#) | [Photonics](#) | [Optical Photonics](#) | [University of Illinois, Urbana-Champaign](#) | [Electrical Equipment](#) | [Energy & Utilities](#) | [Materials](#)


Friday, August 21, 2009

A new process for creating ultrathin, ultrasmall inorganic light-emitting diodes (LEDs) and assembling them into large arrays offers new classes of lighting and display systems with interesting properties, such as see-through construction and mechanical flexibility, that would be impossible to achieve with existing technologies.



Email 0 tweets  
 Print tweet

Applications for the arrays, which can be printed onto flat or flexible substrates ranging from glass to plastic and rubber, include general illumination, high-resolution home theater displays, wearable health monitors, and biomedical imaging devices.



Stretchable micro-LED display, consisting of an interconnected mesh of printed micro LEDs bonded to a rubber substrate. | Photo by D. Stevenson and C. Conway, Beckman Institute, University of Illinois

"Our goal is to marry some of the advantages of inorganic LED technology with the scalability, ease of processing and resolution of organic LEDs," said John Rogers, the Flory-Founder Chair Professor of [Materials Science and Engineering](#) at the University of Illinois.

Rogers and collaborators at the U. of I., Northwestern University, the Institute of High Performance Computing in Singapore, and Tsinghua University in Beijing describe their work in the Aug. 21 issue of the journal *Science*.

Compared to organic LEDs, inorganic LEDs are brighter, more robust and longer-lived. Organic LEDs, however, are attractive because they can be formed on flexible substrates, in dense, interconnected arrays. The researchers' new technology combines features of both.

"By printing large arrays of ultrathin, ultrasmall inorganic LEDs and interconnecting them using thin-film processing, we can create general lighting and high-resolution display systems that otherwise could not be built with the conventional ways that inorganic LEDs are made, manipulated and assembled," Rogers said.

To overcome requirements on device size and thickness associated with conventional wafer dicing, packaging and wire bonding methods, the researchers developed epitaxial growth techniques for creating LEDs with sizes up to 100 times smaller than usual. They also developed printing processes for assembling these devices into arrays on stiff, flexible and stretchable substrates.

As part of the growth process, a sacrificial layer of material is embedded beneath the LEDs. When fabrication is complete, a wet chemical etchant removes this layer, leaving the LEDs undercut from the wafer, but still tethered at anchor points.

To create an array, a rubber stamp contacts the wafer surface at selected points, lifts off the LEDs at those points, and transfers them to the desired substrate.

"The stamping process provides a much faster alternative to the standard robotic 'pick and place' process that manipulates inorganic LEDs one at a time," Rogers said. "The new approach can lift large numbers of small, thin LEDs from the wafer in one step, and then print them onto a substrate in another step."

By shifting position and repeating the stamping process, LEDs can be transferred to other locations on the same substrate. In this fashion, large light panels and displays can be crafted from small LEDs made in dense arrays on a single, comparatively small wafer. And, because the LEDs can be placed far apart and still provide sufficient light output, the panels and displays can be nearly transparent. The thin device geometries allow the use of thin-film processing methods, rather than wire bonding, for interconnects.

SIEMENS

Water Technologies



Latest News

[more](#)

[Juneau schools to turn away kids without shots](#)  
7 hours ago

[Union says talks with are Goodyear progressing](#)  
7 hours ago

[USM and Hanoi National University of Education \(HNUE\) in collaboration to promote next generation internet technologies](#)  
8 hours ago

[Some aspects of birding not always environmentally friendly](#)  
9 hours ago

[Ultrathin LEDs create new classes of lighting\(2\)](#)  
9 hours ago

Advertisement

R&D Magazine and the LABORATORY DESIGN NEWSLETTER Webcast Series

Sponsored by: **SIEMENS**

Reducing Environmental Impact and Energy Consumption for Greener Laboratories

**VIEW FREE TODAY**

Related Stories

[Safest Design Helps Miniaturization of electronics](#)

Aug 25 | News

In addition to solid-state lighting, instrument panels and display systems, flexible and even stretchable sheets of printed LEDs can be achieved, with potential use in the health-care industry.

"Wrapping a stretchable sheet of tiny LEDs around the human body offers interesting opportunities in biomedicine and biotechnology," Rogers said, "including applications in health monitoring, diagnostics and imaging."

The work relied critically on broad, collaborative efforts at the U. of I. In addition to Rogers, the efforts included [electrical and computer engineering](#) professors Xiuling Li, an expert in epitaxial growth, and Kent Choquette, a leader in semiconductor optoelectronics. [Mechanical science and engineering](#) professor Placid Ferreira developed the printing-based manufacturing tools.

Theoretical collaborators at Northwestern University, led by professor Younggang Huang, and at Tsinghua University, under the guidance of Younggang's father, professor Keh-chih Hwang, supported the project through calculations of mechanical strains in the flexible and stretchable systems. Researchers at the Institute for High Performance Computing in Singapore provided finite-element studies of the same systems.

"This sort of broadly interdisciplinary, integrated effort was essential for a successful outcome," Rogers said. "It would be extremely difficult to replicate this type of project at any place other than at the U. of I."

Rogers is affiliated with the [Beckman Institute](#), the department of mechanical science and engineering, the [Frederick Seitz Materials Research Laboratory](#), and the [Micro and Nanotechnology Laboratory](#).

Ford Motor Co., the National Science Foundation and the U. S. Department of Energy funded the work.

[SOURCE](#)

**JOIN THE DISCUSSION**

Rate Article: Average 0 out of 5

[Register](#) or [log in](#) to comment on this article!

0 COMMENTS

ADD COMMENT

Text Only 2000 character limit

Add Comment

Page 1 of 1

**Organic electronics a two-way street**

Aug 18 | News

**Cell phone resonators to go smaller still with MEMS**

Aug 11 | News


**Challenges remain for piezoelectric future**

Jul 28 | News

**Must-Haves**  
for a  
**Changing**  
**Lab Design**  
**Market**

**SIEMENS**  
Water Technologies  
**Lab Water**  
**Solutions**

**Must-Haves**  
for a  
**Changing**  
**Lab Design**  
**Market**



[Magazine/ Newsletters](#)

[Customer Service](#)

[Digital Issue](#)

**New To Market**

[more](#)

**New bioceramic developed by Morgan Technical Ceramics**

Jul 28

Morgan Technical Ceramics has developed a new bioceramic material for surgical implant devices. Vitox AMC is an alumina matrix composite material which can withstand high shock without fracture.

**ExxonMobil to Launch Biofuels Program**

Jul 28

Exxon Mobil Corporation announced an alliance with biotech company, Synthetic Genomics Inc., to research and develop next generation biofuels5 from photosynthetic algae.

**Tools & Technology**

[more](#)



**Temperature sensing chips for high precision applications**

Aug 28

The Temperature Products Group of Measurement Specialties (MEAS) announced the availability of surface mounted devices for varied contact temperature sensing applications. The Ni1000Si is a nickel thin film resistance temperature detector (RTD) that is suitable for use in contact sensing.

**Falling ball viscometer measures Newtonian liquid**

Aug 28

The Brookfield Falling Ball Viscometer measures viscosity in accordance with the test method defined in DIN 53015 (Höppler principle) to measure the viscosity of Newtonian liquid by measuring the time required for a ball to fall under gravity through a sample-filled tube.

**Semiconductor Process**

Advanced technical ceramic material Plasma Etching, CVD, Lithography  
[www.Ceradyne.com](#)

**Avnet- Oled**

Design & Supply Chain Solutions. Start Power-Sourcing w/ Avnet Today  
[www.EM.Avnet.com/StandardProducts](#)

**Silicon Wafer Dicing Svc**

Syagrus Systems quick turn low cost wafer dicing & grinding services.  
[www.syagrussystems.com](#)

V V



- [Bioscience Technology](#)
- [Chromatography Techniques](#)
- [Drug Discovery & Development](#)
- [Pharmaceutical Processing](#)
- [Laboratory Equipment](#)
- [Scientific Computing](#)
- [Lab Design News](#)

Information:

- [About Us](#) | [Contact Us](#) | [Advertise With Us](#)
- [Sitemap](#) | [Privacy Policy](#)
- [Terms & Conditions](#)

Stay in Touch:

- [Newsletters](#)
- [RSS Feeds](#)
- [Mobile](#)
- [Podcasts](#)
- [Blogs](#)